



A ST-LUC COMPANY

Specification requirements

In order to process your artwork quickly and smoothly we detail below our up to date specification requirements. If you have any questions regarding this do not hesitate to call us on the number at the bottom of this page. In order to be sure that you are sending us your data in the required format please call.

- Printing process: ***Flexographic printing / letterpress***
- System: Apple MacOSX
- E-mail: pre.press@altrif.nl
- FTP: - ftp.altrif.com
Login gegevens kunnen opgevraagd worden via ons e-mailadres: pre.press@altrif.nl
- Data carriers: - CD
- DVD
- Application: - ESKO Software Suite 16.0.2
- Adobe Illustrator up to and including CC
- Adobe Photoshop up to and including CC
- Adobe Indesign up to and including CC
- Adobe Acrobat professional 10.0
- Fonts We prefer the tekst in outlines. note: we can't correct or adjust text converted to outline.
If you deliver fonts please send all the fonts used in the artwork even it's Helvetica or Futura.
Every font in a separate folder.

General technical

- We prefer (certified pdfs).
- If you import scans, adaptations like rotating, blowing-up, reducing, lateral reversal need to first be applied in Photoshop, and then imported in used programs.
- Scans minimum 300 dpi, to be saved as TIFF/EPS/PSD).
- To overrun: start from 1% (never from/to 0%).
- Bleeding minimal 1,5mm.
- There should be sufficient trapping between the colours of 0,5pt.
- White text or object **not** on overprint.
- Diapositive text not smaller then 4 points.

General

- Please send a composition (in connection with text control and text break-off) and the last approved colour-separated print. We maintain PMS-norms for spot colours.
- Cutterline in spotcolour (100M/100Y) and name it **CUTTER**. (Kapitals).
- Cutter on overprint.
- White and varnish as separate spotcolours.
- Depending of the artwork the screen ruling is **54 (133 lpi)**, **ruling 60 (154 lpi)** or **ruling 69 (175 lpi)**.
- Dotshape is circular.

letterpress

- ruling 60 (154 lpi)
- ruling 69 (175 lpi)

flexographic printing

- ruling 54 (133 lpi)

Altrif Label BV

Gewenten 39, 4704 RE Roosendaal, The Netherlands
T. (0)165-562000
E. info@altrif.nl
W. www.altrif.nl

RafCycle®



Only the products that are identified as such on this document are FSC® certified

Het keurmerk voor verantwoord bosbeheer



A ST-LUC COMPANY

Specification requirements

In order to process your artwork quickly and smoothly we detail below our up to date specification requirements. If you have any questions regarding this do not hesitate to call us on the number at the bottom of this page. In order to be sure that you are sending us your data in the required format please call.

- Printing process: **Digital**
- System: Apple MacOSX
- E-mail: pre.press@altrif.nl
- FTP: - ftp.altrif.com
Login gegevens kunnen opgevraagd worden via ons e-mailadres: pre.press@altrif.nl
- Data carriers: - CD
- DVD
- Application: - ESKO Software Suite 16.0.2
- Adobe Illustrator up to and including CC
- Adobe Photoshop up to and including CC
- Adobe Indesign up to and including CC
- Adobe Acrobat professional 10.0
- Fonts We prefer the tekst in outlines. note: we can't correct or adjust text converted to outline.
If you deliver fonts please send all the fonts used in the artwork even it's Helvetica or Futura.
Every font in a separate folder.

General technical

- We prefer (certified pdfs).
- If you import scans, adaptations like rotating, blowing-up, reducing, lateral reversal need to first be applied in Photoshop, and then imported in used programs.
- Scans minimum 300 dpi, to be saved as TIFF/EPS/PSD).
- Bleeding minimal 1,5mm.
- White text or object **not** on overprint.
- Diapositive text not smaller then 4 points.

General

- Please send a composition (in connection with text control and text break-off) and the last approved colour-separated print. We maintain PMS-norms for spot colours.
- Cutterline in spotcolour (100M/100Y) and name it **CUTTER**. (Kapitals).
- Cutter on overprint.
- White and varnish as separate spotcolours.
- Dotshape is circular.

Altrif Label BV

Gewenten 39, 4704 RE Roosendaal, The Netherlands
T. (0)165-562000
E. info@altrif.nl
W. www.altrif.nl

RafCycle®



Only the products
that are identified
as such on this
document are
FSC® certified

Het keurmerk voor
verantwoord bosbeheer